NSN 5905-00-166-8124

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-166-8124

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
1.3910 inches
Pilot Length:
0.0620 inches
Overall Length:
2.155 inches
Undercut Diameter:
1.875 inches
Undercut Width:
0.2770 inches
Body Diameter:
2.016 centimeters
Shaft Diameter:
0.2497 inches
Shaft Length:
1.250 inches
Body Length:
0.905 inches
Overall Diameter:
2.500 inches
Mounting Lip Diameter:
2.0160 inches
Mounting Lip Depth:
0.0780 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
280.0
Maximum Starting Torque:
0.70 inch-ounces
Maximum Running Torque:
0.60 inch-ounces

NSN 5905-00-166-8124

Shaft End Play:

Precision Wire Wound Variable Resistor - Page 2 of 3



0.005 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.002 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
5.0 percent, rated amperes c and better flooring
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
140.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
10.0 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
7 oclock all primaries
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20 0/±20 0 single section

-20.0/+20.0 single section

NSN 5905-00-166-8124

Precision Wire Wound Variable Resistor - Page 3 of 3



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Special Features: One fixed resistor, 5.1k ohms, 1 w rating, externally mtd between terminals Terminal Type And Quantity: 4 turret Shelf Life: N/a Unit Of Measure: ---

No

Demilitarization:

Fiig:

A002a0