NSN 5905-00-168-9318

Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-168-9318 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Overall Length:** 3.813 inches **Body Diameter:** 1.219 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.500 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 2.313 inches **Overall Diameter:** 1.094 inches **Undercut Diameter:** 0.125 inches **Shaft Style:** Round, stepped **Shaft Bearing Type:** Bearing Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type: Dual concentric Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Maximum Stop Torque:** 128.00 inch-ounces **Nonturn Device Location:**

At 12 oclock

Nonturn Device Radius:

0.359 inches

NSN 5905-00-168-9318

Switch Operating Position:

Nonprecision Wire Wound Variable Resistor - Page 2 of 3



Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Fragility Factor:
Rugged
Undercut Length:
0.500 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
500.000 ohms 2nd section
Rotary Actuator Travel In Angular Deg:
320.0
Function Conformity Tolerance Per Section:
-3.00 to 3.00 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Power Dissipation Rating Per Section In Watts:
4.0 free air 1st section
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
All sections linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 all sections
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

2.000 ac

60.0 all sections

Switch Current Type And Rating In Amps:

NSN 5905-00-168-9318

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



Unpackaged Unit Weight:
1.25 ounces
Terminal Type And Quantity:
8 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0