Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-172-0856

| Section | Quantity: |
|---------|-----------|

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

**Overall Length:** 

1.172 inches

**Overall Height:** 

0.500 inches

**Body Length:** 

1.172 inches

Body Width:

0.969 inches

Body Height:

0.500 inches

Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

360.0

**Fragility Factor:** 

Rugged

**Terminal Location:** 

Radially positioned over less than half the circumference

#### **Mounting Method:**

Tab

#### **Electrical Resistance Per Section:**

100.0 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

360.0

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

#### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-1000.0 to 1000.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

### **Resistance Tolerance Per Section In Percent:**

-30.0 to 30.0 single section

### **Actuator Travel Control Feature:**

Continuous motion

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

AeroBase Group

Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0