## NSN 5905-00-172-7964

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-172-7964 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.96830 inches and 0.96880 inches Pilot Length: 0.06200 inches **Overall Length:** 1.466 inches **Undercut Diameter:** 0.975 inches **Undercut Width:** 0.05700 inches **Body Diameter:** 1.125 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.625 inches **Body Length:** 0.810 inches **Overall Diameter:** 1.562 inches **Mounting Lip Diameter:** 1.06200 inches **Mounting Lip Depth:** 0.06200 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0

**Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.40 inch-ounces **Shaft End Play:** 0.005 inches

## NSN 5905-00-172-7964

N/a

**Unit Of Measure:** 

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Mechanical Backlash In Deg Angular Rotation:
0.5
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Resistance Tempurature Characteristic Range Per Section In Percent:
-5.0/+5.0 -65 degrees celsius single section and -2.5/+2.5 50 degrees celsius single section and -5.0/+5.0 75 degrees celsius single section
and -5.0/+5.0 105 degrees celsius single section and -5.0/+5.0 125 degrees celsius single section
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.25 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section 360 degrees sine-cosine
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Test Data Document:
00752-373734 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
6 turret
Shalf Life:

## NSN 5905-00-172-7964

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0