NSN 5905-00-172-8167

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-172-8167

| Section Quantity: |
|---|
| |
| Body Style: |
| Rectangular |
| Terminal Length: |
| 0.172 inches |
| Shaft Diameter: |
| 0.078 inches |
| Shaft Length: |
| 0.045 inches |
| Body Length: |
| 0.540 inches |
| Body Width: |
| 0.205 inches |
| Body Height: |
| 0.500 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| Between 7200.0 and 16200.0 |
| Center To Center Distance Between Terminals: |
| 0.200 inches |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Terminal |
| Electrical Resistance Per Section: |
| 200.000 ohms single section |
| Rotary Actuator Travel In Angular Deg: |
| Between 7200.0 and 16200.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| 0.100 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -250.0 to 250.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.5 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0 to 10.0 single section |

NSN 5905-00-172-8167

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Actuator Travel Control Feature: |
|--|
| Clutch |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 85.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Test Data Document: |
| 81349-milr22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 3 pin |
| Specification Data: |
| 81349-mil-r-22097/3 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |