Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-172-9731

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## Reliability Indicator:

Not established

### **Body Diameter:**

1.125 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.375 inches

### Mounting Bushing Length:

0.250 inches

#### Body Length:

### 2.078 inches

Shaft Style:

#### Round

Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

6120.0

### Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.516 inches

#### Screw Thread Diameter:

0.250 inches

#### **Screw Thread Series Designator:**

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Rear end

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

150.0 ohms single section

# Rotary Actuator Travel In Angular Deg:

6120.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-30.0 to 30.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

3.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

## **Actuator Travel Control Feature:**

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

60.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0