

View Online at https://aerobasegroup.com/nsn/5905-00-173-2699

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Overall Length:**

2.812 inches

### Body Diameter:

1.812 inches

## Shaft Diameter:

0.2497 inches

## Shaft Length:

0.812 inches

## Mounting Bushing Length:

# 0.250 inches

**Body Length:** 

1.938 inches

Shaft Style:

## Round

Actuator Type:

## Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

3600.0

## Nonturn Device Location:

At 12 oclock

## **Nonturn Device Radius:**

0.562 inches

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

10.000 kilohms single section

# Function Conformity Tolerance Per Section:

-0.10 to 0.10 single section



### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

### **Power Dissipation Rating Per Section In Watts:**

5.0 free air single section

## **Function Conformity Per Section:**

Single section independent linearity

# Fixed Tap Quantity Per Section:

9 single section

#### **Tap Location Tolerance Per Section:**

-1.0 to 1.0 degrees angular rotation single section

## **Resistance Tolerance Per Section In Percent:**

-1.0/+1.0 single section

### **Function Characteristic Per Section:**

Single section linear

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

### **Terminal Type And Quantity:**

12 tab, solder lug

### Shelf Life:

N/a

### Unit Of Measure:

--

# Demilitarization:

No

### Fiig:

A002a0