NSN 5905-00-173-4228

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-173-4228

Electrical Resistance: 10.000 kilohms Resistance Tolerance in Percent: -0.001 to 0.010 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: -0.295 inches Body Wildth: -0.320 inches Body Wildth: -0.320 inches Body Height: -0.100 inches Power Dissipation Rating in Watts: -0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6996756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -0.010 to 0.010 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.255 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 frea air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Umit Of Measure:	-5.0 to 5.0
Resistance Tolerance in Percent: -0.010 to 0.010 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating in Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03840-6986756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure:	Electrical Resistance:
-0.010 to 0.010 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.320 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6996756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	10.000 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.325 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03840-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc., excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.300 inches Body Width: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	-0.010 to 0.010
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.390 inches Body Width: 0.300 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6098758 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Width: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Wight: 0.300 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Note Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	175.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Rediability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	-55.0 to 175.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Encapsulated
Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Wire lead
Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.295 inches
Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Width:
0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.320 inches
Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 0.3640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Height:
0.300 free air Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.100 inches
Style Designator: Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Terminals one edge Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.300 free air
Test Data Document: 03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminals one edge
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	03640-6096756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0