NSN 5905-00-173-4810

Nonprecision Wire Wound Variable Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-173-4810 **Section Quantity: Reliability Indicator:** Not established **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Maximum Running Torque:** 3.50 inch-ounces **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 20.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.25 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A002a0