## NSN 5905-00-173-5228

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-173-5228 **Section Quantity:** 3 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 4.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.781 inches **Mounting Bushing Length:** 0.281 inches **Body Length:** 7.250 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 1.25 kilohms 2nd section **Rotary Actuator Travel In Angular Deg:** 300.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 all sections **Power Dissipation Rating Per Section In Watts:** 

150.0 free air all sections

## NSN 5905-00-173-5228

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
9 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: