## NSN 5905-00-173-6067

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-173-6067

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.125 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.469 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
0.500 inches
Fragility Factor:
Fragility Factor: Moderately rugged
Moderately rugged
Moderately rugged Screw Thread Diameter:
Moderately rugged  Screw Thread Diameter:  0.375 inches
Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:
Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef
Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):
Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0
Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:
Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location:  Radially positioned over less than half the circumference
Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location:  Radially positioned over less than half the circumference  Mounting Method:
Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Radially positioned over less than half the circumference  Mounting Method: Standard bushing
Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Radially positioned over less than half the circumference  Mounting Method: Standard bushing  Electrical Resistance Per Section:
Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference  Mounting Method:  Standard bushing  Electrical Resistance Per Section:  500.0 ohms single section

-10.0 to 10.0 single section

## NSN 5905-00-173-6067

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A002a0