NSN 5905-00-173-8091

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-173-8091 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.344 inches Flat Height: 0.219 inches **Body Diameter:** 1.125 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.562 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing

Electrical Resistance Per Section: 1.0 kilohms all sections

NSN 5905-00-173-8091

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts: 2.0 free air all sections Resistance Tolerance Per Section In Percent: -10.0 to 10.0 all sections Standard Taper Curve Per Section: A all sections Terminal Type And Quantity: 12 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization: No

Fiig: A002a0