## NSN 5905-00-173-8621

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-173-8621

-500.0 to 500.0  Electrical Resistance:  15.000 kilohms  Resistance Tolerance In Percent:  -1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  40.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  120.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 105.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established
15.000 kilohms  Resistance Tolerance In Percent: -1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 120.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 105.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established
Resistance Tolerance In Percent: -1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 120.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 105.0  Inclosure Method: Encapsulated Terminal Type: Wire lead  Reliability Indicator: Not established
-1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 120.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 105.0  Inclosure Method: Encapsulated Terminal Type: Wire lead  Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Full Rated Power:  40.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  120.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0 to 105.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  120.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 105.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  120.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 105.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
-55.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established
Terminal Type: Wire lead Reliability Indicator: Not established
Wire lead  Reliability Indicator:  Not established
Reliability Indicator: Not established
Not established
Body Diameter:
0.296 inches
Body Length:
0.937 inches
Power Dissipation Rating In Watts:
1.000 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-milr10509a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0