Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-173-8756

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## **Body Diameter:**

1.156 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

1.000 inches

#### Mounting Bushing Length:

0.375 inches

#### Body Length:

## 0.625 inches

Shaft Style:

Round

#### Actuator Type:

Single shaft

## Nonturn Device Location:

At 3 oclock and at 9 oclock

## Nonturn Device Radius:

0.531 inches

# Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Locking bushing

## **Electrical Resistance Per Section:**

5.0 kilohms single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Standard Taper Curve Per Section:

A single section



## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0