NSN 5905-00-173-8764

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-173-8764

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.313 inches
Body Diameter:
1.063 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.563 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Standard Taper Curve Per Section:
A single section

NSN 5905-00-173-8764

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A002a0