NSN 5905-00-173-9032

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-173-9032

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.125 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.938 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.594 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing
Features Provided:
Shaft locking device
Electrical Resistance Per Section:
2.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:

A single section

NSN 5905-00-173-9032

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity	/ :
----------------------------	------------

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0