NSN 5905-00-173-9260

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-173-9260

| Section Overtibus |
|---|
| Section Quantity: |
| |
| Body Style: |
| Cylindrical bushing mounted |
| Reliability Indicator: |
| Not established |
| Body Diameter: |
| 1.125 inches |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 0.625 inches |
| Mounting Bushing Length: |
| 0.500 inches |
| Body Length: |
| 0.594 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Nonturn Device Location: |
| At 9 oclock |
| Nonturn Device Radius: |
| 0.531 inches |
| Fragility Factor: |
| Moderately rugged |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 10.0 kilohms single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Resistance Tolerance Per Section In Percent: |

-10.0 to 10.0 single section

NSN 5905-00-173-9260

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Standard Taper Curve Per Section |
|----------------------------------|
| A single section |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A002a0