Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-173-9288

## Section Quantity:

2

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Body Diameter:**

1.156 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.375 inches

#### Body Length:

## 1.266 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Radius:

0.531 inches

## Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

500.000 kilohms 2nd section

#### **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 1st section

## Standard Taper Curve Per Section:

A single section

### **Terminal Type And Quantity:**

6 tab, solder lug

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0