Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-173-9952

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Overall Length:**

2.438 inches

### **Body Diameter:**

1.063 inches

### Shaft Diameter:

0.250 inches

### Shaft Length:

1.875 inches

## Mounting Bushing Length:

0.375 inches

### Body Length:

# 0.563 inches

Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

## Nonturn Device Location:

At 3 oclock and at 9 oclock

# Nonturn Device Radius:

0.531 inches

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

10.000 kilohms single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0