NSN 5905-00-174-1422

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-174-1422

Section Quantity:
2
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.438 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.000 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.062 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.530 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
120.0 kilohms all sections
Power Dissipation Rating Per Section In Watts:
2.0 free air all sections
Resistance Tolerance Per Section In Percent:

A all sections

-20.0 to 20.0 all sections

Standard Taper Curve Per Section:

NSN 5905-00-174-1422

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0