NSN 5905-00-174-2442

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-174-2442

2.000 kilohms Resistance Tolerance In Percent: -5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Not rated Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Not rated Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Not rated Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Not rated Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Not rated Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Ferrule Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Not established Terminal Length: 0.500 inches Body Diameter: Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Terminal Length: 0.500 inches Body Diameter: Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
0.500 inches Body Diameter: Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Body Diameter: Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Between 0.688 inches and 1.062 inches Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Body Length: 4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
4.125 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
50.000 free air Style Designator: Axial terminal each end Shelf Life: N/a
Style Designator: Axial terminal each end Shelf Life: N/a
Axial terminal each end Shelf Life: N/a
Shelf Life: N/a
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0