Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-174-4789

Saction	Quantity:
Section	Quantity.

1

**Reliability Indicator:** 

Not established

## Shaft Diameter:

0.125 inches

Shaft Length:

0.438 inches

#### Mounting Bushing Length:

0.375 inches

Shaft Style:

Round, slotted

### Shaft Bearing Type:

Bearing

#### Actuator Type:

Single shaft

# Nonturn Device Location:

At 9 oclock

#### **Nonturn Device Radius:**

0.234 inches

# Screw Thread Diameter:

0.250 inches

### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

#### **Mounting Method:**

Locking bushing

### **Electrical Resistance Per Section:**

5.000 kilohms single section

### **Power Dissipation Rating Per Section In Watts:**

0.2 free air single section

### **Function Conformity Per Section:**

Single section independent linearity

### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

### Standard Taper Curve Per Section:

C single section

## **Terminal Type And Quantity:**

3 tab, solder lug

Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0