NSN 5905-00-174-4903

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-174-4903 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.594 inches Flat Height: 0.219 inches **Body Diameter:** 1.156 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.266 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing

Electrical Resistance Per Section: 15.0 kilohms all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

NSN 5905-00-174-4903

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 all sections
Standard Taper Curve Per Section:
F all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:

Demilitarization:

Unit Of Measure:

No

N/a

Fiig:

A002a0