## NSN 5905-00-174-5096

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-174-5096 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.125 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.500 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.594 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** 0.531 inches **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 

5.0 kilohms single section

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

## NSN 5905-00-174-5096

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Standard Taper Curve Per Section |
|----------------------------------|
| A single section                 |
| Terminal Type And Quantity:      |
| 3 tab, solder lug                |
| Shelf Life:                      |
| N/a                              |
| Unit Of Measure:                 |
|                                  |
| Demilitarization:                |
| No                               |

**Fiig:** A002a0