## NSN 5905-00-175-5566

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-175-5566

Section Quantity:
1
Body Style:
Cylindrical studs mounted
Reliability Indicator:
Not established
Overall Length:
2.625 inches
Body Diameter:
3.781 inches
Shaft Diameter:
0.2495 inches
Shaft Length:
0.469 inches
Body Length:
2.094 inches
Overall Diameter:
4.000 inches
Mounting Hole/stud Circle Diameter:
1.250 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
310.0
Maximum Starting Torque:
3.00 inch-ounces
Maximum Running Torque:
1.50 inch-ounces
Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:

Threaded hole

## NSN 5905-00-175-5566

Precision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
20.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
320.0
Function Conformity Tolerance Per Section:
-0.33 to 0.33 single section
Power Dissipation Rating Per Section In Watts:
6.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
20.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
N/a Unit Of Measure:
· · ·
· · ·
Unit Of Measure:
Unit Of Measure: Demilitarization:
Unit Of Measure: Demilitarization: