NSN 5905-00-175-5576

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-175-5576 **Section Quantity:** 1 **Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Body Diameter:** 1.312 inches **Shaft Diameter:** 0.375 inches **Shaft Length:** 0.250 inches **Body Length:** 0.969 inches **Mounting Hole/stud Circle Diameter:** 0.625 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Fragility Factor:** Moderately rugged **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Unthreaded hole **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 20.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 25.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 threaded stud

Shelf Life:

Onen Ene

N/a

NSN 5905-00-175-5576

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0