

View Online at https://aerobasegroup.com/nsn/5905-00-175-5593

## Section Quantity:

1

Body Style:

Cylindrical servo mounted

## **Reliability Indicator:**

Not established

#### Pilot Diameter:

1.87500 inches

#### **Pilot Length:**

0.06200 inches

### **Undercut Diameter:**

1.875 inches

#### **Undercut Width:**

0.06200 inches

#### **Body Diameter:**

2.109 inches

### Angle Of Mounting Hole In Deg:

90.0

#### Angle Between Centerlines Of Mounting Holes In Deg:

120.0

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.625 inches

#### **Body Length:**

1.412 inches

#### Mounting Lip Diameter:

2.00000 inches

#### Mounting Lip Depth:

0.06200 inches

#### Mounting Hole/stud Circle Diameter:

0.875 inches

#### Shaft Style:

Round

## Shaft Bearing Type:

Ball

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

300.0

## Maximum Starting Torque:

2.00 inch-ounces



#### Maximum Running Torque:

1.00 inch-ounces

#### Shaft End Play:

0.00150 inches

#### Shaft Runout:

0.001 inches

## Lateral Runout:

0.001 inches

#### Pilot Diameter Runout:

0.00150 inches

#### Shaft Radial Play:

0.001 inches

#### Screw Thread Diameter:

0.164 inches

#### Screw Thread Series Designator:

Unc

## Screw Thready Qty Per Inch (tpi):

32.0

## **Mounting Facility Quantity:**

3

## Terminal Location:

#### Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

## Features Provided:

Nonmetallic shaft

#### **Electrical Resistance Per Section:**

3.000 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

310.0

# Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

# Power Dissipation Rating Per Section In Watts:

3.0 free air single section

# Function Conformity Per Section:

Single section independent linearity

# **Resistance Tolerance Per Section In Percent:**

-1.0 to 1.0 single section

# Actuator Travel Control Feature:

Stops

# Function Characteristic Per Section:

Single section linear



## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

20.0 single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0