NSN 5905-00-175-5606

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-175-5606

Section Quantity:
1
Body Style:
Cylindrical studs mounted
Reliability Indicator:
Not established
Body Diameter:
3.719 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.469 inches
Body Length:
2.094 inches
Mounting Hole/stud Circle Diameter:
1.250 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
13.562 kilohms single section
Power Dissipation Rating Per Section In Watts:
6.0 free air single section
Fixed Tap Quantity Per Section:
1 single section

Tap Location Tolerance Per Section:

-0.5 to 0.5 degrees angular rotation single section

NSN 5905-00-175-5606

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistaı	nce '	Tolerance	e Per	Section	In Percent

-0.4 to 0.4 single section

Tap Location From Ccw Terminal Per Section In Ohms:

6781.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0