## NSN 5905-00-175-5607

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-175-5607 **Section Quantity: Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Overall Length:** 1.719 inches **Body Diameter:** 2.656 inches **Mounting Hole Diameter:** 0.164 inches **Shaft Diameter:** 0.049 inches **Shaft Length:** 0.062 inches **Body Length:** 1.188 inches **Overall Diameter:** 3.000 inches **Mounting Hole/stud Circle Diameter:** 1.500 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Screw Thread Diameter:** 0.164 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity: Terminal Location:** 

Radially positioned over less than half the circumference

## NSN 5905-00-175-5607

Precision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Threaded hole
Electrical Resistance Per Section:
19.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
310.0
Function Conformity Tolerance Per Section:
-0.33 to 0.33 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
225.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-0.5/+0.5 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
20.0 single section
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<b></b>
Demilitarization:
Yes - demil/mli
Fiig:
A002a0