## NSN 5905-00-175-5624

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-175-5624

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.812 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.954 inches
Mounting Bushing Length:
0.250 inches
Body Length:
1.125 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock
At 3 oclock  Nonturn Device Radius:
Nonturn Device Radius:
Nonturn Device Radius: 0.531 inches
Nonturn Device Radius: 0.531 inches Fragility Factor:
Nonturn Device Radius: 0.531 inches Fragility Factor: Moderately rugged
Nonturn Device Radius:  0.531 inches  Fragility Factor:  Moderately rugged  Screw Thread Diameter:
Nonturn Device Radius:  0.531 inches  Fragility Factor:  Moderately rugged  Screw Thread Diameter:  0.375 inches
Nonturn Device Radius:  0.531 inches  Fragility Factor:  Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:
Nonturn Device Radius:  0.531 inches  Fragility Factor:  Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef
Nonturn Device Radius:  0.531 inches  Fragility Factor:  Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):
Nonturn Device Radius:  0.531 inches  Fragility Factor:  Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0
Nonturn Device Radius:  0.531 inches  Fragility Factor:  Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:
Nonturn Device Radius:  0.531 inches  Fragility Factor:  Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference
Nonturn Device Radius:  0.531 inches  Fragility Factor:  Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference  Mounting Method:
Nonturn Device Radius:  0.531 inches  Fragility Factor:  Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference  Mounting Method:  Standard bushing
Nonturn Device Radius:  0.531 inches  Fragility Factor:  Moderately rugged  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference  Mounting Method:  Standard bushing  Electrical Resistance Per Section:
Nonturn Device Radius:  0.531 inches Fragility Factor: Moderately rugged Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 5.0 kilohms single section

-10.0 to 10.0 single section

## NSN 5905-00-175-5624

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Terminal Type And Quantity:
3 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0