

View Online at https://aerobasegroup.com/nsn/5905-00-175-5629

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Body Diameter:**

1.812 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.500 inches

#### Mounting Bushing Length:

0.312 inches

#### Body Length:

## 1.220 inches

Shaft Style:

### Round

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

1080.0

## Maximum Starting Torque:

1.75 inch-ounces

#### Maximum Running Torque:

1.25 inch-ounces

### Fragility Factor:

Moderately rugged

#### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Longitudinally positioned on the circumference

# Mounting Method:

Standard bushing

# **Features Provided:**

Nonmetallic shaft

## **Electrical Resistance Per Section:**

5.0 kilohms single section



Function Conformity Tolerance Per Section:

-0.50 to 0.50 single section

### **Power Dissipation Rating Per Section In Watts:**

3.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

Function Characteristic Per Section:

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

#### Fiig:

A002a0