Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-175-5679

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Overall Length:

0.530 inches

Overall Height:

0.500 inches

Overall Width:

0.190 inches

Mounting Slot Width:

0.093 inches

Shaft Diameter:

0.083 inches

Shaft Length:

0.030 inches

Body Length:

0.500 inches

Body Width:

0.190 inches

Body Height:

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

5.00 inch-ounces

Lateral Distance Between Mounting Hole Centers:

0.520 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Slot

Electrical Resistance Per Section:

500.000 ohms single section

Rotary Actuator Travel In Angular Deg:

9000.0



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-30.0 to 30.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

95542-138-062 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

--

Fiig:

A002a0