

View Online at https://aerobasegroup.com/nsn/5905-00-175-5850

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Overall Length:**

1.810 inches

#### **Body Diameter:**

0.870 inches

#### Shaft Diameter:

0.250 inches

## Shaft Length:

0.810 inches

## Mounting Bushing Length:

# 0.250 inches

**Body Length:** 

1.000 inches

## **Overall Diameter:**

1.055 inches

## Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

## Maximum Starting Torque:

0.60 inch-ounces

## Maximum Stop Torque:

96.00 inch-ounces

## Shaft End Play:

0.005 inches

#### Shaft Runout:

0.002 inches

## Lateral Runout:

0.005 inches

#### **Pilot Diameter Runout:**

0.002 inches

#### Shaft Radial Play:

0.003 inches

## **Fragility Factor:**

Moderately rugged

## Screw Thread Diameter:

0.375 inches

Unef

32.0

Stops

N/a

---

No Fiig: A002a0



**Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft and shaft seal **Electrical Resistance Per Section:** 25.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.20 to 0.20 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature: Function Characteristic Per Section:** Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Test Data Document:** 18876-10233416 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: Unit Of Measure: **Demilitarization:**