## NSN 5905-00-175-7434

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-175-7434

Resistance Tolerance in Percent: 5.000 to 5.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Incapsulated Ferminal Type: Incapsulated Ferminal Length: 0.375 inches 30dy Diameter: 0.375 inches 30dy Length: 1.750 inches 30dy Length: 3.000 free air Ferminal Width: 3.028 inches 33dy Designator: Radial terminal each end Iest Data Document: 313d9-millz6/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 2xcludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). 3cheff Life: 3cheff L	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0 Inclosure Method: Encapsulated Ferminal Type:  16.0, solder lug Ferminal Length:  10.375 inches  30dy Diameter:  10.375 inches  30dy Diameter:  10.375 inches  30dy Diameter:  10.375 inches  30dy Diameter:  10.375 inches  30dy Length:  10.750 inches  Power Dissipation Rating In Watts:  10.300 free air  Ferminal Width:  10.328 inches  3x8y Designator:  Radial terminal each end  Fest Data Document:  13349-mil/26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  3cheff Life:  1/40  2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2	1.000 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  276.0  276.0  277.0  278.0  279	-5.000 to 5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  nolosure Method:  Encapsulated  ferminal Type:  Tab, solder lug  ferminal Length:  1.375 inches  30dy Diameter:  1.375 inches  30dy Length:  1.750 inches  30dy Ength:  30dy Eng	Ambient Tempurature In Deg Celsius At Full Rated Power:
nclosure Method: Encapsulated Ferminal Type: Flab, solder lug Ferminal Length: 10,375 inches 380dy Diameter: 10,375 inches 380dy Length: 1.750 inches 70 wer Dissipation Rating In Watts: 1.750 inches 70 wer Dissipation Rating In Watts: 1.750 inches 810 year Dissipation Rating In Watts: 1.750 inches 810 year Dissipation Rating In Watts: 1.750 inches 810 year Dissipation Rating In Watts: 1.750 inches 1.750 i	25.0
Inclosure Method: Encapsulated Ferminal Type: Tab, solder lug Ferminal Length: 0.375 inches 8.304y Diameter: 0.375 inches 8.304y Length: 1.750 inches 8.304y Length: 1.750 inches 8.309 Power Dissipation Rating In Watts: 8.300 free air Ferminal Width: 8.328 inches 8.319 Designator: 8.328 inches 8.349 Designator: 8.3418 about Length: 8.349-milr26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). 8.364eff Life: 9.40 9.40 9.40 9.40 9.40 9.40 9.40 9.40	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Forminal Type:  Fab, solder lug  Ferminal Length:  1.375 inches  3.375 inches  3.375 inches  3.375 inches  3.375 inches  3.375 inches  3.30dy Length:  1.750 inches  Power Dissipation Rating In Watts:  3.300 free air  Ferminal Width:  3.328 inches  Style Designator:  Radial terminal each end  Fest Data Document:  1.375 inches excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Shelf Life:  Via  Juit Of Measure:  Demilitarization:  No  Filig:	275.0
Terminal Type:  Tab, solder lug  Terminal Length:  1.375 inches  3.375 i	Inclosure Method:
Fab, solder lug  Ferminal Length:  0.375 inches  Body Diameter:  0.375 inches  Body Diameter:  0.375 inches  Body Length:  1.750 inches  Body	Encapsulated
Ferminal Length: 0.375 inches 80dy Diameter: 0.375 inches 80dy Length: 0.750 inches 80dy Length:	Terminal Type:
Body Diameter:  0.375 inches  Body Length:  1.750 inches  Power Dissipation Rating In Watts:  0.000 free air  Ferminal Width:  0.328 inches  Byle Designator:  Radial terminal each end  Fest Data Document:  81349-milr26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:  No  Pigg:	Tab, solder lug
Body Length: 1.750 inches Power Dissipation Rating In Watts: 1.750 inches Power Dissipation Rating In Watts: 1.750 inches Power Dissipation Rating In Watts: 1.750 inches 1.75	Terminal Length:
3.375 inches 3.30dy Length: 1.750 inches 2.76wer Dissipation Rating In Watts: 3.000 free air 1.750 inches 3.000 inche	0.375 inches
Body Length:  1.750 inches  Power Dissipation Rating In Watts:  3.000 free air  Ferminal Width:  3.288 inches  Style Designator:  Radial terminal each end  Fest Data Document:  81349-milr26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:  No  Fig:	Body Diameter:
Power Dissipation Rating In Watts: 3.000 free air Ferminal Width: 3.328 inches Style Designator: Radial terminal each end Fest Data Document: 3.349-milr26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Junit Of Measure: Demilitarization: No	0.375 inches
Power Dissipation Rating In Watts: 3,000 free air  Ferminal Width: 0,328 inches  Style Designator: Radial terminal each end  Fest Data Document: 3,1349-milr26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  W/a  Junit Of Measure: - Demilitarization: No	Body Length:
Reminal Width:  0.328 inches  Style Designator:  Radial terminal each end  Fest Data Document:  81349-milr26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:  No  Fig:	1.750 inches
Terminal Width:  0.328 inches  Style Designator:  Radial terminal each end  Test Data Document:  81349-milr26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:  No  Fig:	Power Dissipation Rating In Watts:
2.328 inches  Style Designator: Radial terminal each end  Fest Data Document: B1349-milr26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure: - Demilitarization: No  Fig:	8.000 free air
Style Designator: Radial terminal each end Fest Data Document: 31349-milr26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No Filig:	Terminal Width:
Radial terminal each end  Fest Data Document:  81349-milr26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:  No  Fig:	0.328 inches
Fest Data Document:  81349-milr26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  -  Demilitarization:  No  Fig:	Style Designator:
B1349-milr26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Radial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Cemilitarization:  No  Fiig:	81349-milr26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a  Jnit Of Measure: - Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a  Jnit Of Measure:  - Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization: No -iig:	Shelf Life:
- Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	<del></del>
Filg:	Demilitarization:
	No
	Fiig:
<del>\</del> 001a0	A001a0