Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-175-8650

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Overall Length:**

1.937 inches

### Body Diameter:

0.968 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.812 inches

### Mounting Bushing Length:

# 0.375 inches

**Body Length:** 

0.375 inches

Shaft Style:

Round

Switch Type:

Push-pull

#### Switch Voltage Rating In Volts:

125.0

Actuator Type:

Single shaft

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

#### **Switch Operating Position:**

Any position of rotation travel

#### Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

#### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Rear-bottom



**Mounting Method:** Standard bushing **Features Provided:** Switch **Electrical Resistance Per Section:** 200.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section Switch Current Type And Rating In Amps: 3.000 ac/dc **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 5 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0