

View Online at <https://aerobasegroup.com/nsn/5905-00-175-8651>

Section Quantity:

1

Body Style:

Cylindrical friction mounted

Reliability Indicator:

Not established

Body Diameter:

0.783 inches

Shaft Diameter:

0.156 inches

Shaft Length:

0.438 inches

Body Length:

0.328 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Maximum Starting Torque:

4.00 inch-ounces

Maximum Running Torque:

0.75 inch-ounces

End Application:

Forrestal class cv, austin ship class lpd-4 amphibious transport docks, whidbey island class lsd, nimitz class cvn, emory s.Land class as, spruance class d (963), tarawa class lha, supply class aoe, oliver perry class ffg, virginia class cgn(41)

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Tab

Electrical Resistance Per Section:

1.5 megohms single section

Power Dissipation Rating Per Section In Watts:

0.1 free air single section

Resistance Tolerance Per Section In Percent:

-30.0 to 30.0 single section

Criticality Code Justification:

Feat

Standard Taper Curve Per Section:

A single section

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0