## NSN 5905-00-180-4567

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-180-4567 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.1247 inches **Shaft Length:** 0.563 inches **Body Length:** 1.536 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Shaft End Play:** 0.005 inches **Fragility Factor:** Moderately rugged **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 10.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -20.0 to 20.0 single section **Power Dissipation Rating Per Section In Watts:** 

1.0 free air single section **Fixed Tap Quantity Per Section:** 

1 single section

## NSN 5905-00-180-4567

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## **Tap Location Tolerance Per Section:** -1.0 to 1.0 ohms single section **Resistance Tolerance Per Section In Percent:** -1.0 to 1.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 turret Shelf Life: N/a **Unit Of Measure:** Demilitarization: No