Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-180-8626

Section Quantity:

1

Body Style:

Cylindrical friction mounted

Reliability Indicator:

Not established

Thread Length:

0.750 inches

Body Diameter:

0.500 inches

Mounting Hole Diameter:

0.220 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.810 inches

Body Length:

5.000 inches

Shaft Style:

Round, threaded

Actuator Type:

Single shaft

Longitudinal Actuator Travel:

2.968 inches

Longitudinal Actuator Effective Electrical Stroke Length:

2.812 inches

Fragility Factor:

Moderately rugged

Mounting Facility Quantity:

4

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Features Provided:

Hermetically sealed

Electrical Resistance Per Section:

500.0 ohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section



Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

2 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0