

View Online at <https://aerobasegroup.com/nsn/5905-00-180-8998>

Section Quantity:

2

Body Style:

Rectangular w/bushing

Reliability Indicator:

Not established

Shaft Diameter:

0.247 inches

Shaft Length:

1.740 inches

Mounting Bushing Length:

0.438 inches

Body Length:

3.500 inches

Body Width:

1.250 inches

Body Height:

1.820 inches

Undercut Diameter:

0.122 inches

Shaft Style:

Round, stepped

Switch Type:

Rotary

Switch Voltage Rating In Volts:

120.0

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

285.0

Nonturn Device Radius:

0.625 inches

Switch Operating Position:

Any position of rotation travel

Switch Contact Arrangement:

Single pole, double throw, three positions maintained

Fragility Factor:

Moderately rugged

Undercut Length:

0.650 inches

Screw Thread Diameter:

0.438 inches

Screw Thread Series Designator:

Uns

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Features Provided:

Switch

Electrical Resistance Per Section:

2.5 kilohms all sections

Rotary Actuator Travel In Angular Deg:

285.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

Power Dissipation Rating Per Section In Watts:

5.0 free air all sections

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Switch Current Type And Rating In Amps:

2.000 ac/dc

Standard Taper Curve Per Section:

A all sections

Special Features:

Three switches

Terminal Type And Quantity:

15 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0