## NSN 5905-00-185-9929

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-185-9929

Section Quantity:
1
Body Style:
Cylindrical, edge control operated
Reliability Indicator:
Not established
Body Diameter:
0.625 inches
Mounting Stud Length:
0.145 inches
Body Length:
0.296 inches
Actuator Type:
Integral knob
Screw Thread Diameter:
0.073 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
72.0
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
250.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
260.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
0.1 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section

## NSN 5905-00-185-9929

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig:

A002a0