Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-186-0538

# Section Quantity:

1

Body Style:

Cylindrical tab/flange mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.775 inches

#### **Body Length:**

0.420 inches

#### Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

240.0

## Fragility Factor:

Moderately delicate

### Lateral Distance Between Mounting Hole Centers:

1.000 inches

### **Terminal Location:**

Rear end

#### Mounting Method:

Flange

#### **Electrical Resistance Per Section:**

500.0 ohms single section

## Rotary Actuator Travel In Angular Deg:

240.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

2.5 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## Actuator Travel Control Feature:

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

### Standard Taper Curve Per Section:

A single section

### **Terminal Type And Quantity:**

3 wire lead

#### Shelf Life:

N/a

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0