## NSN 5905-00-186-3073

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-186-3073

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Cylindrical hole/slot mounted                             |
| Reliability Indicator:                                    |
| Not established   |
| First Flat Length:  |
| 1.562 inches  |
| Flat Height:  |
| 0.344 inches  |
| Body Diameter:  |
| 5.000 inches  |
| Shaft Diameter:   |
| 0.375 inches  |
| Shaft Length:   |
| 2.000 inches  |
| Body Length:  |
| 2.125 inches  |
| Mounting Hole/stud Circle Diameter:                       |
| 1.750 inches  |
| Shaft Style:  |
| Round, flatted  |
| Actuator Type:  |
| Single shaft  |
| Screw Thread Diameter:                                    |
| 0.250 inches  |
| Screw Thread Series Designator:                           |
| Unc   |
| Screw Thready Qty Per Inch (tpi):                         |
| 20.0  |
| Mounting Facility Quantity:                               |
| 2   |
| Terminal Location:  |
| Radially positioned over less than half the circumference |
| Mounting Method:  |
| Threaded hole   |
| Electrical Resistance Per Section:                        |
| 32.000 ohms single section                                |
| Power Dissipation Rating Per Section In Watts:            |
| 225.0 free air single section                             |
| Resistance Tolerance Per Section In Percent:              |

-10.0 to 10.0 single section

## NSN 5905-00-186-3073

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig: A002a0