NSN 5905-00-186-5009

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-186-5009

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.875 inches
Shaft Diameter:
0.375 inches
Shaft Length:
0.938 inches
Body Length:
1.250 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
1080.0
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
1.203 inches
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Terminal
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
175.000 ohms single section
Rotary Actuator Travel In Angular Deg:
1080.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
12.0 free air single section
Resistance Tolerance Per Section In Percent:
-3.0 to 3.0 single section

NSN 5905-00-186-5009

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: