Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-187-9644

# Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

#### Body Length:

0.187 inches

#### **Body Width:**

0.500 inches

**Body Height:** 

0.500 inches

#### Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

260.0

### **Terminal Location:**

Rear end

### **Mounting Method:**

Terminal

### **Electrical Resistance Per Section:**

1.5 kilohms single section

### Rotary Actuator Travel In Angular Deg:

260.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0 to 70.0 single section

### **Power Dissipation Rating Per Section In Watts:**

0.2 free air single section

**Resistance Tolerance Per Section In Percent:** 

-0.1 to 0.1 single section

### **Actuator Travel Control Feature:**

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

# Standard Taper Curve Per Section:

A single section

## **Terminal Type And Quantity:**

3 wire lead

#### Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0