

View Online at <https://aerobasegroup.com/nsn/5905-00-188-3029>

Section Quantity:

1

Body Style:

Rectangular w/mounting hole/slot

Reliability Indicator:

Not established

Terminal Length:

0.300 inches

Mounting Hole Diameter:

0.074 inches

Shaft Diameter:

0.090 inches

Shaft Length:

0.040 inches

Body Length:

0.390 inches

Body Width:

0.250 inches

Body Height:

0.390 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

7200.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches

Mounting Facility Quantity:

1

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal and unthreaded hole

Cubic Measure:

0.038 cubic inches

Electrical Resistance Per Section:

50.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

7200.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

75.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

15786-97676 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0