NSN 5905-00-188-3858

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-188-3858 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8130 inches Pilot Length: 0.0620 inches **Overall Length:** 1.875 inches **Undercut Diameter:** 1.844 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.875 inches **Mounting Hole Diameter:** 0.120 inches **Angle Of Mounting Hole In Deg:** 90.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.625 inches **Body Length:** 1.250 inches **Overall Diameter:** 2.241 inches **Mounting Lip Diameter:** 1.8750 inches **Mounting Lip Depth:** 0.0620 inches **Mounting Hole/stud Circle Diameter:** 1.203 inches **Shaft Style:** Round

Shaft Bearing Type: Ball

NSN 5905-00-188-3858

Precision Wire Wound Variable Resistor - Page 2 of 3



Contact Arm Electrical Off Position:
Fully ccw
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
1080.0
Maximum Starting Torque:
1.30 inch-ounces
Maximum Running Torque:
0.90 inch-ounces
Shaft End Play:
0.005 inches
Shaft Runout:
0.0005 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Fragility Factor:
Moderately rugged
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
1080.0
Function Conformity Tolerance Per Section:
-0.25 to 0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:

-15.0/+15.0 ohms single section

NSN 5905-00-188-3858

A002a0

Precision Wire Wound Variable Resistor - Page 3 of 3



Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Tap Location From Ccw Terminal Per Section In Ohms:
5000.0 single section
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: