## NSN 5905-00-188-4338

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-188-4338

Tempurature Coe	fficient Of Resis	stance In Ppm	Per Deg Celsius:
-----------------	-------------------	---------------	------------------

-50.0/+50.0

**Electrical Resistance:** 

0.110 ohms

**Resistance Tolerance In Percent:** 

-1.000 to 1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

25.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.0

**Tempurature Range Of Tempurature Coefficient In Deg Celsius:** 

-55.0 to 275.0

**Inclosure Method:** 

Encased

**Terminal Type:** 

Tab, solder lug

**Reliability Indicator:** 

Not established

**Terminal Length:** 

Between 0.376 inches and 0.500 inches

**Body Length:** 

Between 1.876 inches and 2.000 inches

**Body Width:** 

Between 0.532 inches and 0.656 inches

**Body Height:** 

Between 0.594 inches and 0.656 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.552 inches and 1.572 inches

**Power Dissipation Rating In Watts:** 

10.000 free air

**Mounting Hole Size:** 

Between 0.120 inches and 0.130 inches

Cubic Measure (non-core):

0.781 cubic inches

**Unpackaged Unit Weight:** 

32.0 grams

Style Designator:

Axial terminal (s)

## **Test Data Document:**

81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-18546/1 government specification

## NSN 5905-00-188-4338

Inductive Wire Wound Fixed Resistor - Page 2 of 2



She	lf L	.if	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0