## NSN 5905-00-192-0703



Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5905-00-192-0703
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.187 inches
Body Diameter:
1.062 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.562 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0

**Mounting Method:** 

Locking bushing

**Electrical Resistance Per Section:** 

10.000 kilohms single section

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section

**Function Conformity Per Section:** 

Single section independent linearity

## NSN 5905-00-192-0703

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resista	nce To	lerance	Per :	Section	In Percen	ıt:

-10.0 to 10.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

**Reference Number Differentiating Characteristics:** 

As differentiated by the electrical resis-tance specified

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0