NSN 5905-00-192-1029

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-192-1029 **Section Quantity: Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.281 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.512 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 1.300 ohms 2nd section **Power Dissipation Rating Per Section In Watts:** 25.0 free air all sections **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 1st section **Standard Taper Curve Per Section:** A 1st section **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5905-00-192-1029

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0