Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-192-1036

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Body Diameter:**

1.062 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

0.750 inches

Mounting Bushing Length:

0.350 inches

#### Body Length:

0.562 inches

Shaft Style:

Round

Actuator Type:

Single shaft

#### Fragility Factor:

Moderately rugged

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### **Mounting Method:**

Standard bushing

#### **Features Provided:**

Humidity proof

#### **Electrical Resistance Per Section:**

3.0 kilohms single section

## Power Dissipation Rating Per Section In Watts:

3.0 free air single section

### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

### Standard Taper Curve Per Section:

A single section



# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0